

HYLOAD ASPHALT PRIMER



1. PRODUCT NAME

Hyload Asphalt Primer

This unique product is a precise blend of oxidized asphalt and refined solvents which penetrates porous surfaces, creating a bondable substrate thus ensuring proper adhesion of subsequent layers.

2. MANUFACTURER

Hyload, Inc.
9976 Rittman Road
Wadsworth, Ohio 44281
Phone (800) 457-4056
Fax (330) 769-4153

3. ADVANTAGES

1. The excellent qualities of this product allow it to adhere to most dry surfaces.
2. Creates a bondable surface on masonry, concrete, wood, gypsum and most metals.
3. Asbestos free formulation.

4. SURFACE PREPARATION

Areas to be primed must be free of dirt, dust, oil and other debris.

5. APPLICATION

Hyload Asphalt Primer may be applied using a soft roller or brush.

6. COVERAGE

Depending on the condition of the surface to be primed, coverage may vary from 150-200 square feet per gallon.

7. CAUTION

1. Harmful or fatal if swallowed.
2. For exterior use only.
3. Contains petroleum distillate.
4. Keep away from heat and flame.
5. Keep away from children.
6. Read all labels and warnings.

For additional information:

Hyload, Inc.
5020 Panther Parkway
Seville, Ohio 44273

Phone: 800-457-4056
Fax: 330-769-4153
Website: www.hyloadflashing.com